



A3 DTG T-Shirt Printer



Direct to Garment

Super Reliable
超稳定

White Circulation
白墨循环

High Speed
速度快


Easy to Use
易于使用

● Features 特点



SinoColor System. Much more professional and more stable than desktop modified printer. Control the color freely.

SinoColor System 相比改装机更多功能可实现, 色彩控制更加随心所欲。




White ink circulation and stirring system are equipped. Reduce problem caused by White ink precipitation.

配备白墨搅拌和循环系统, 减少因白墨沉淀造成的问题。




Well-designed touch screen. Easily Adjust platform position.

精心设计的触摸屏, 轻松调整平台位置。



Automatic media height detecting system is standard equipped. Simplify the setting of proper platform height.

标配自动测高。



Maximumly use mold to produce machine components to achieve amazing resolution.

最大程度模具化生产设备组件以达到最高的精度。



● Specification 参数

Model No.	型号	TP-300i	TP-300D	TP-600i	TP-600D
Printhead	打印喷头	1×Epson Head	2×Epson i1600 Heads	1×Epson Head	2×Epson i1600 Heads
Resolution	打印精度	1440dpi	2400dpi	1440dpi	2400dpi
Ink Color	墨水颜色	CMYK	CMYK + W	CMYK	CMYK + W
Max Speed	打印速度	2 minutes for one T-shirt			
Print Head Height	喷头高度	10 cm Max			
Printing Size	打印尺寸	30×40 cm Max		40×60 cm Max	
Print Direction	打印方向	Intelligence double side			
Print Method	打印方法	Micro piezo print technology, intelligence drops transformation technology			
Height Adjust	高度调节	Electric			
Distance of Print Head Printing		1-3 mm (1 mm is the best)			
Ink Supply System	供墨系统	CISS			
Ink Consumption	墨水消耗	15-20 ml / square meter (1 liter print about 500PCS T-shirt)			
Min Ink Drop Size	墨滴大小	< 1.5 PL			
Interface	输入接口	USB 3.0			
Rip Software	图像处理	Maintop (Standard) / FlexiPRINT (Optional)			
Working Environment	工作环境	Temperature 18-30 Celsius, Humidity 30-70 RH, Clean room, Low dust, Less sun light			
Power	电源输入	AC 110/220 V, 50 Hz/60 Hz			
Size & Weight	Machine 机器	L670×W565×H635 mm / 110KG		L770×W765×H635 mm / 120KG	
	Packing 包装	L900×W820×H650 mm / 120KG		L1150×W950×H680 mm / 150KG	

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。