



COMPACT

DTF GARMENT PRINTING SOLUTION

—
Epson i3200/ i1600

- ▶ 2/ 3/ 4 Epson Heads
- ▶ CMYK + W + Fluorescent Color
- ▶ Printing + Powder Treating
- ▶ 40cm/ 60cm/ 80cm



• Features



Compact Integrated Design

Compact and elegant design, strong, space saving, easy operation, provide high accuracy output. Not only one partner for your printing business, but also a decoration for the company.



High Quality Components

Branded accessories such as Hiwin guide rail, Italian Megadyne belt are used for high attrition area, with the one time molding aluminum beam, greatly increased the precision, stability and lifetime of the machine.




Integrated Control Centre

Convenient and high-efficiency.



Anti-collision System

Printer will automatically stop when the printhead carriage hits any unexpected object during working, and the system memory function supports continuing printing from the interruption part, reducing the material waste.



Multifunctional Machine for Mass Production

Apply to different fabric include cotton, polyester, nylon, denim, etc. Make the mass production of DIY t-shirts, hoodies, sportswear, pants, canvas bag to be convenient.



• Specification

| Model No. | DTF-600D | DTF-600S | DTF-800D | DTF-800S | |
|--------------------------------|--|---------------------------------|---------------------------------|-------------------------------|----------------------------------|
| Printhead | 2/3/4 Epson i1600 | 2/3/4 Epson i3200 | 2/3/4 Epson i1600 | 2/3/4 Epson i3200 | |
| Resolution | 2400dpi | 2400dpi | 2400dpi | 2400dpi | |
| Ink Color | CMYK+W/ CMYK+W+Fluorescent Magenta & Yellow & Green & Orange | | | | |
| Media | Size | 60cm | | 80cm | |
| | Types | PET Film | | | |
| Speed | Draft | 8 m ² /h (2 heads) | 19 m ² /h (4 heads) | 9 m ² /h (2 heads) | 21 m ² /h (4 heads) |
| | Standard | 4.5 m ² /h (2 heads) | 9.5 m ² /h (4 heads) | 5 m ² /h (2 heads) | 11.5 m ² /h (4 heads) |
| Ink Type | Pigment Ink | | | | |
| Application | DIY Printing On T-shirt, Hoodies, Cap, Bag, Etc. | | | | |
| Ink Droplet | 1.5-21pl Variable | | | | |
| Powder Shaking And Heating | Standard Equipped | | | | |
| Powder Collecting And Re-using | Standard | | | | |
| Built-in Smoke Filter | Optional | | | | |
| Cleaning | Automatic Cleaning, Anti-Clogging Flash Function & Capping System | | | | |
| Feed & Take Up | Automatic Media Feeding (Standard) & Take Up System (Standard) | | | | |
| Environment | Temperature: 20-28°C, Humidity: 40%-60% | | | | |
| Rip Software | Maintop (Standard) / FlexiPRINT (Optional) | | | | |
| Interface | USB 3.0 | | | | |
| Power | AC 110/ 220V, 50/ 60Hz, 3400W | | | | |

Specifications are subject to change without notice. 以上参数可能随机器版本改变, 请以厂家最新数据为准。